

BC/OC 1" Tweeter




Type Number: AC25SG05-04

Features:

The BC/OC product line is known for its quality tweeters and midwoofers. Designed in Denmark by our experienced team of audio engineers, Peerless BC/OC products can meet the most demanding needs for both volume and audio excellence. The BC/OC product line has ferrofluid in the magnet gap for improved cooling of the driver.

Driver Highlights: Textile tweeter, shielded ferrite magnet, alu face plate



Specs:

Electrical Data

Nominal impedance	Zn	4	ohm
Minimum impedance	Zmin	--	ohm
Maximum impedance	Zo	--	ohm
DC resistance	Re	3	ohm
Voice coil inductance	Le	--	mH

T-S Parameters

Resonance Frequency	fs	1100	Hz
Mechanical Q factor	Qms	2.9	
Electrical Q factor	Qes	1.5	
Total Q factor	Qts	1	
Force factor	Bl	2.2	Tm
Mechanical resistance	Rms	--	Kg/s
Moving mass	Mms	0.33	g
Suspension compliance	Cms	--	mm/N
Effective cone diameter	D	--	cm
Effective piston area	Sd	6.8	cm ²
Equivalent volume	Vas	--	ltrs
Sensitivity (2.83V/1m)		--	dB

Power handling

Long-term Max Power (IEC 18.3)	90	W
Short Term Max power (IEC 18.2)	--	W

Voice Coil and Magnet Parameters

Voice coil diameter	25	mm
Voice coil height	1.8	mm
Voice coil layers	2	
Height of the gap	3	mm
Flux density of gap	--	mWb
Total useful flux	--	mWb
Diameter of magnet	70	mm
Height of magnet	15	mm
Weight of magnet	--	Kg

Notes:
IEC specs refer to IEC 60268-5 third edition.
All Tymphany products are RoHS compliant.

Frequency:

Mechanical Dimensions:

