

## BC/OC 1" Tweeter



Type Number: DQ25SC05-04

### Features:

The BC/OC product line is known for its quality tweeters and midwoofers. Designed in Denmark by our experienced team of audio engineers, Peerless BC/OC products can meet the most demanding needs for both volume and audio excellence. The BC/OC product line has ferrofluid in the magnet gap for improved cooling of the driver.

Driver Highlights: Neodymium titanium tweeter, rear heatsink



### Specs:

#### Electrical Data

Nominal impedance	Zn	4	ohm
Minimum impedance	Zmin	--	ohm
Maximum impedance	Zo	--	ohm
DC resistance	Re	3	ohm
Voice coil inductance	Le	0.017	mH

#### T-S Parameters

Resonance Frequency	fs	1320	Hz
Mechanical Q factor	Qms	3.36	
Electrical Q factor	Qes	1.68	
Total Q factor	Qts	1.12	
Force factor	Bl	--	Tm
Mechanical resistance	Rms	--	Kg/s
Moving mass	Mms	--	g
Suspension compliance	Cms	--	mm/N
Effective cone diameter	D	--	cm
Effective piston area	Sd	6.6	cm <sup>2</sup>
Equivalent volume	Vas	--	ltrs
Sensitivity (2.83V/1m)		94	dB

#### Power handling


Long-term Max Power (IEC 18.3)	50	W
Short Term Max power (IEC 18.2)	--	W

#### Voice Coil and Magnet Parameters

Voice coil diameter	25.4	mm
Voice coil height	1.8	mm
Voice coil layers	2	
Height of the gap	2	mm
Flux density of gap	--	mWb
Total useful flux	--	mWb
Diameter of magnet	25	mm
Height of magnet	3.5	mm
Weight of magnet	--	Kg

Notes:  
IEC specs refer to IEC 60268-5 third edition.  
All Tympany products are RoHS compliant.

## Frequency: DQ25SC05-04



## Mechanical Dimensions: DQ25SC05-04

